


X-TREME Anschlagpunkt

TWN 1830



- + Güteklasse 10
- + In Gewindeabmessungen von M10 - M56 verfügbar
- + Volle Belastbarkeit in alle Zugrichtungen
- + Durch integriertes Kugellager für Hebe- und Wendevorgänge gut geeignet
- + Unter Last drehbar
- + Kompakte Bauweise
- + Lieferung mit Gewindetransportschutz
- + Optimaler Oberflächenschutz
- + Einfache Montage durch Maulschlüssel
- + 100% rissgeprüft
- + 3D-Daten auf CADENAS-Plattform erhältlich
- + BG-Zulassung (GS M0 15-04) 



THIELE GmbH & Co. KG

Werkstr. 3 · 58640 Iserlohn · Germany

THIELE.de · hebetechnik@THIELE.de

2 +49 2371 947-0


5 +49 2371 947-241



X-TREME Lifting Point

TWN 1830



- + Grade 100
- + In thread size M10 - M56 available
- + Full Load Limit in all pulling directions
- + Due to integrated ball bearing very good appropriated for Lifting and Turnaround applications
- + Turnable under load
- + Compact design
- + Thread transport protection
- + Optimal surface protection
- + Fast assembly with standard jaw spanner
- + 100% crack tested
- + 3D-Data on CADENAS-Platform available
- + Occupational accidental insurance approved (GS M0 15-04) 



THIELE GmbH & Co. KG

Werkstr. 3 · 58640 Iserlohn · Germany

THIELE.de · hebetechnik@THIELE.de

2 +49 2371 947-0

5 +49 2371 947-241

